



## MCCB 140G J FRAME LESS TRIP UNIT 25kA 4P

- Wide range of fault interruption ratings from 25 to 200kA to cater for a wide spectrum of applications
- MCCB sizes available from 16 to 3000A with various common frames and common accessories which simplifies use
- Customer-fit accessories available to enable quick and easy configuration for almost all project types
- Basic or Advanced OCR's such AC/DC thermal magnetic, AC electronic, to suit varied installation requirements.
- Worldwide support from Rockwell-Allen Bradley for IEC or UL related projects

Representative Photo Only  
(actual product may vary based on configuration selections)

### SPECIFICATIONS

Product Series	Bul. 140G & 140MG
Component Type MCCB	Breaker Frame
Un, Nominal Operational Voltage, AC	690 V AC
Ics, Rated Service Short-Circuit Breaking Capacity, 220V AC	65 kA
Ics, Rated Service Short-Circuit Breaking Capacity, 415V AC	36 kA @415VAC
Ics, Rated Service Short-Circuit Breaking Capacity, 440V AC	36 kA
Ics, Rated Service Short-Circuit Breaking Capacity, 690V AC	10 kA @690VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 220V AC	65 kA @220VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 415V AC	36 kA @415VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 440V AC	36 kA @440VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 690V AC	10 kA @690VAC
Frame Size	Frame J size
Ui, Rated Insulation Voltage	800 V (rms)
Reverse Connection Of Supply Possible	Yes
Altitude, Operating (Derating)	5000 m
Altitude, Operating (No Derating)	2000 m

Catalogue No: **140G-J2X4**

**MCCB 140G J FRAME LESS TRIP UNIT 25kA 4P**

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Allen-Bradley 140G Moulded Case Circuit Breakers > J Frame 250AF MCCB > Less Trip Unit 25kA



#### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -